

5	RJ45防水硅胶塞 $\phi 11.8 \times \phi 6 \times 8$ E13 Waterproof silicone plug $\phi 11.8 \times \phi 6 \times 8$	硅胶 plastic	黑色 Black	pc	1
4	RJ45防水垫片 $\phi 18.6 \times 1.5$ RJ45 Waterproof gasket	硅胶 silica gel	黑 Black	pc	1
3	RJ45插头紧锁螺帽 RJ45 Locking nut	PA66	黑 Black	pc	1
2	RJ45插头线孔 RJ45 Plug wire hole	PA66	黑色 Black	pc	1
1	RJ45连接螺帽 RJ45 Connecting nut	PA66	黑色 Black	pc	1
No.	Specification	Material	Treat	Unit	Q'ty


技术参数(Technical specifications):

传输速率: transmission rate	符合TIA或EIA 568B的5E类/6A类D级/等级和符合ISO/IEC 11801 CAT5E/6A ,According to TIA or EIA 568B,According to ISO/IEC 11801
防水等级: Degree of protection	IP67
接触电阻: Contact resistance	$\cong 20m\Omega$
绝缘电阻: Insulation resistance	$\cong 500M\Omega$ at DC500V
工频耐电压: Withstand voltage	$\cong AC 1000V / 1$ 分钟 $\cong AC 1000V / 1$ minute
盐雾腐蚀: Salt spray corrosion	48小时 48 hours
POE:	60W / 2A

20.10.10
Date

GENERAL TOLERANCE (UNLESS SPECIFIED)

≤ 10	± 0.1
$< 10 \sim \leq 20$	± 0.2
$< 20 \sim \leq 50$	± 0.5
Angle	$\pm 1^\circ$



THIRD ANGLE

DWN	
CHK	
APVD	
UNIT MM	REV A
SIZE A4	SHEET 1 OF 1

CAZN 正成

TITLE
RJ45-A

PART NO

DRAWING NO